

Floor cleaner TD 410 INDUSTRIAL with suction system, TD 410 INDUSTRIAL and TD 410 BASIC



The choice of perfection

Complete
stainless
design

turbodevil

- » Especially designed for professional cleaning applications
- » Max. 60 °C. 1,000 r.p.m. at 3 - 60 °C

turbodevil
INDUSTRIAL

- » Especially designed for industrial cleaning applications
- » For hot water use of up to 120 °C. 2,000 r.p.m. at 5 - 120 °C

new

TD 410
also as Version
INDUSTRIAL
for professional
industrial
cleaning
applications!

ST-2600 **LTF**

We recommend
using the gun
ST-2600 with
patented LTF
technology.

The new turbodevil floor cleaner TDI 410 with suction system, TDI/TD 410

- Working width 410 mm.
- With foldable handle bar for space saving and reasonable transport.
- 2 nozzles 1/4" M are required.
- Precision rotor, welded by robots
- 3 robust industrial castors: Ø 60 mm.
- Max. temperature: 60 / 120 °C
- Max. pressure: 275 bar
- Flow: 1,800 l/h

TD 410
with suction system

Model
Ø 420 mm
with 3 castors



Pleasant handle:
ergonomic
shaped.



Swivel:
with 3-ball
bearing swivel.
Our version
INDUSTRIAL is
equipped with
ceramic or
tungsten carbide
sealing elements
for high durability
and extremely long
stress.



**3 industrial
castors (60 mm):**
easy and
flexible steering
Our version
INDUSTRIAL is
equipped with industrial
stainless steel castors.



Precision rotor:
welded by robots



Suction system: The splash guard
is specially designed for the best suction.

Floor cleaner TD 410 INDUSTRIAL with suction system, TD 410 INDUSTRIAL and TD 410 BASIC



The choice of perfection

Surface cleaner TD 410 BASIC



Surface cleaner with foldable handle bar for space saving and reasonable transport. Swivel with triple bearing system.

3 industrial castors (60 mm).

2 nozzles 1/4" M are required.

Max. 1,800 l/h / 60 °C. Max. 275 bar

R+M Nr.	Ø	G	P
521 042 350	410 mm	1/4" F	max. 275 bar

Surface cleaner TD 410 INDUSTRIAL



Surface cleaner with foldable handle bar for space saving and reasonable transport. Swivel with triple bearing system and ceramic sealing elements.

3 stainless steel industrial castors (60 mm).

2 nozzles 1/4" M are required.

Max. 1,800 l/h / 120 °C. Max. 275 bar

R+M Nr.	Ø	G	P
521 042 450	410 mm	1/4" F	max. 275 bar

Surface cleaner TD 410 INDUSTRIAL with suction system



EXTRA robust 3-ball bearing swivel: with tungsten carbide sealing elements for high durability.

Surface cleaner with foldable handle bar for space saving and reasonable transport. Very robust swivel with triple bearing system and tungsten carbide sealing elements. 3 stainless steel industrial castors (60 mm).

2 nozzles 1/4" M are required.

Max. 1,800 l/h / 120 °C. Max. 275 bar

R+M Nr.	Ø	G	P
521 042 500	410 mm	1/4" F	max. 275 bar

High pressure nozzles

1/4" M NPT, 15 °

D	R+M Nr.
02	613 05
025	613 07
03	613 10
04	613 30
045	613 40
05	613 50



Impact = 100 %