Nozzle holder ST-330, pivotable and lockable







Pivoting nozzle holder with locking screw

- Inlet M18
- For large flow rates up to 45 l / min.
- Maximum pressure: 310 bar
- Maximum temperature: 150 ° C
- Equipped with a cross grip screw made of polyamide / stainless steel to lock the swivel position.
- Including nozzle holder for nozzle tips (catalog, chapter 11)
- Further pivoting and lockable ST-330 versions without nozzle holder can be found on the following page





High pressure telescopic lances: A large selection, infinitely extendable, up to 7.4 m can be found in the catalog, chapter 10.

Perfect for high pressure telescopic lances:

To ensure safe handling, set the water jet at a shallow angle first and increase it gradually as required. (The angular water jet generates a torque on the high pressure gun)



Stainless steel.
Max. 310 bar / 45 l/min / 150 °C


R+M Nr.	Θ	E	
200 330 521	tip nozzle	18 x 1.5 F	

Nozzle holder ST-330, pivotable and lockable



ST-330 swivel nozzle holder

- » Swivel it easily!
- » Used for cleaning of places which are difficult to access such as container e.g. feeding troughs and gutters.
- » Effortless and variable shifting of the swivel direction.
- » Completely made out of stainless steel.
- » Capable of swivelling by up to 240°.









Stainless steel. Max. 310 bar / 45 l/min / 150 °C

R+M Nr.	Θ	Œ.
200 330 500	1/4" F NPT	1/4" F
200 330 510	1/4" M	1/4" F



Stainless steel.

Max. 310 bar / 45 l/min / 150 °C

R+M Nr.	Θ	C
200 330 501	1/4" F NPT	1/4" F
200 330 511	1/4" M	1/4" F



Stainless steel.
Max. 310 bar / 45 l/min / 150 °C

R+M Nr.	Θ	E
200 330 521	tip nozzle	M18 F



Stainless steel. Max. 310 bar / 45 l/min / 150 °C

R+M Nr.	Θ	E
200 330 600	tip nozzle	M18 F