

## ST-247 coupling system

The new high-pressure hose and lance coupling system ST-247 can be added to existing high-pressure cleaning systems and provides for quick and reliable changing of accessories without any annoying screwing and jamming.

Thanks to its intuitive operation and very sturdy design, it offers all advantages of a quick coupling system.

Being made of a high-quality combination of brass and stainless steel, it is perfectly suitable for use in professional or industrial environments such as agriculture and cleaning of large surfaces ranging from transporters to public places and outside surfaces.

Thanks to the plastic coating of the handwheels, the coupling system is ideally suited for hot-water applications.

## ST-247 couplings



Brass. TR22 F. Max. 400 bar / 150° C.

R+M Nr. 200 247 310



ST-247 : 1/4" M. Hardened stainless steel. Max. 400 bar / 150° C.

R+M Nr. 200 247 110



TR22 F. Brass. Incl. 2 heat resistant caps. Max. 400 bar / 150° C.

ST-247:1/4 "F.

R+M Nr.

200 247 100

Hardened stainless steel.

Max. 400 bar / 150° C.

R+M Nr. 200 247 410



M22 F. Brass. Incl. 1 heat resistant cap. Max. 400 bar / 150° C.

R+M Nr. 200 247 420



ST-247. Brass. Max. 310 bar / 45 l/min / 150 °C



ST-247 : M22 M. Hardened stainless steel. Max. 400 bar / 150° C

R+M Nr. 200 247 125



ST-247 : TR22 M. Brass/stainless steel. Max. 400 bar / 150° C.

R+M Nr.

200 247 255

R+M Nr. 200 247 120