


SITE CLEANING EQUIPMENT

Powder Coated Hose Reels by TEHA

Manual Rewind




Automatic Spring Rewind



Model	1	2	3	4	Weight
75014	440mm	400mm	176mm	206mm	14kg
75020	500mm	460mm	176mm	206mm	16kg
75030	500mm	460mm	226mm	256mm	18kg
75040	500mm	460mm	276mm	306mm	25kg
7502019	500mm	460mm	176mm	206mm	17kg
7504019	500mm	460mm	376mm	406mm	26.5kg

Hose Size	Capacity	Inlet/Outlet	Rating	Part No
DN8	24m	3/8" F	400 bar, 90C	76020
	36m	3/8" F	400 bar, 90C	76030
DN10	19m	3/8" F	400 bar, 90C	76020
	28m	3/8" F	400 bar, 90C	76030



Model	1	2	3	4	Weight
76020	437mm	400mm	210mm	100mm	6.2kg
76030	500mm	460mm	210mm	100mm	6.8kg


Hose Size	Capacity	Inlet/Outlet	Rating	Part No
DN8	14m	3/8" F	400 bar, 90C	75014
	20m	3/8" F	400 bar, 90C	75020
	30m	3/8" F	400 bar, 90C	75030
	40m	3/8" F	400 bar, 90C	75040
DN10	12m	3/8" F	400 bar, 90C	75014
	17m	3/8" F	400 bar, 90C	75020
	26m	3/8" F	400 bar, 90C	75030
	35m	3/8" F	400 bar, 90C	75040
DN19	10m	3/4" F	200 bar, 90C	7502019
	35m	3/4" F	200 bar, 90C	7504019

Stainless Steel Hose Reels by TEHA

Manual Rewind




Automatic Spring Rewind



Model	1	2	3	4	Weight
74014	440mm	400mm	176mm	206mm	14kg
74020	500mm	460mm	176mm	206mm	16kg
74030	500mm	460mm	226mm	256mm	18kg
74040	500mm	460mm	276mm	306mm	25kg
74060	500mm	460mm	376mm	406mm	32.5kg
7402012	500mm	460mm	176mm	206mm	16kg
7404012	500mm	460mm	276mm	306mm	25kg
7404019	500mm	460mm	376mm	406mm	26.5kg

Hose Size	Capacity	Inlet/Outlet	Rating	Part No
DN12	35m	1/2" F	300 bar, 90C	73950
	70m	1/2" F	300 bar, 90C	73960
	100m	1/2" F	300 bar, 90C	73965
	115m	1/2" F	300 bar, 90C	7397012
DN19	40m	3/4" F	200 bar, 90C	7396019



Model	1	2	3	4	Weight
73950	515mm	465mm	280mm	312mm	10.5kg
73960	515mm	465mm	480mm	512mm	13.5kg
73965	515mm	465mm	680mm	712mm	15.7kg
7397012	515mm	465mm	780mm	812mm	16.8kg
7396019	515mm	465mm	480mm	512mm	14.7kg

Hose Size	Capacity	Inlet/Outlet	Rating	Part No
DN8	14m	3/8" F	400 bar, 90C	74014
	20m	3/8" F	400 bar, 90C	74020
	30m	3/8" F	400 bar, 90C	74030
	40m	3/8" F	400 bar, 90C	74040
	55m	3/8" F	400 bar, 90C	74060
DN10	12m	3/8" F	400 bar, 90C	74014
	17m	3/8" F	400 bar, 90C	74020
	26m	3/8" F	400 bar, 90C	74030
	35m	3/8" F	400 bar, 90C	74040
	48m	3/8" F	400 bar, 90C	74060
DN12	17m	1/2" F	300 bar, 90°C	7402012
	35m	1/2" F	300 bar, 90°C	7404012
DN19	35m	3/4" F	200 bar, 90C	7404019