

TRICOFLEX®



Flexible multilayer hose.

Advantages

Exterior covering in ultra UV resistant PVC. With woven polyester fibre reinforcement and two-layer smooth lining.

1 2 Yellow PVC covering

3

4 5 Smooth black two-layer inner tube

Woven fibre reinforcement

The multilaver design, made of an exclusive woven fibre and a double core layer, ensures that Tricoflex is highly flexible for easy handling, with excellent resistance to repeated bending, crushing and pulling as well as minor deformation under pressure.

In addition, the lining is extremely smooth, thereby maintaining even flow. Especially thick and made of high quality materials, Tricoflex offers remarkable ageing resistance with exceptional preservation of flexibility. Its exterior yellow PVC covering gives it good protection against abrasion and UV rays.

Connectors

Connectors with band, screw or 'O' type clamps. Automatic connectors for watering.

Chemical resistance

See table pages 64 to 67 column A.

Applications

- Irrigation
- Water supply and delivery

Sectors of activity

- Farms
- Vegetable growers
- Horticulture
- Water supply and delivery in industry, construction sites and road works
- Gardening

Marking: TRICOFLEX

(2)	Ø	(<u>)</u> -			M	Yellow		
mm	mm	mm		Bar	mm"	25 m	50 m	100 m
12,5	18	2,75	25	10	125	117135	117151	117016
15	20,5	2,75	25	10	135	116861	116874	054426
19	25,5	3,25	23	9,2	180	116887	051546	054437
25	32,5	3,75	20	8	240	048273	048374	048363
30	39	4,5	20	8	300	048508	048510	048497
35	45	5	20	8	350	048565	048554	048587
40	51	5,5	20	8	400	048442	048453	048655
50	63	6,5	20	8	500	048306	048341	