

CARWASH COMFORT Premium



The choice of perfection

Ideal for
the use in professional
car cleaning



CARWASH COMFORT Premium – now even more flexible for use in self-service car washes

- Extremely flexible and elastic high-pressure hose, thanks to a special plastic compound.
- Experience the new orange miracle in use, maximum durability and flexibility for perfect vehicle care.
- Highest resistance to oil, UV-, ozone- and weatherproof
- Flexible in case of low temperatures: -40 °C – +60 °C, -40 °F – +140 °F
- High-tensile polyester reinforcing, working pressure of up to 200 bar with a fourfold guarantee that the hose does not burst
- Outer diameter 12.8 mm at DN 6
- Burst pressure > 800 bar

TEST the BEST

Excellent sliding properties,
flexibility and durability!



Aufbau: PES, Polyester und Elastomer



Bend protection: Now also available
in orange.

Premium

Quality from professionals
for professionals:

After many tests and extensive research work, we have added an extremely bend-friendly and highly flexible hose to our program for use in the self-service washing area, thanks to a special plastic combination. This is unsurpassedly smooth and a very good choice for handling in perfect vehicle care.

Test our new CARWASH COMFORT
in new premium quality!



Carwash Solutions made in Germany: Color-coordinated quality-products from R+M / Suttner, convincing and durable.

www.rm-suttner.com

CARWASH COMFORT Premium

CARWASH COMFORT Premium

1/4" : 1/4"



new

3/8" : 3/8"



new

M14 : M14



new

M18 : M18



new

3/8" : 3/8"



new

Female thread (DKR)

R+M Nr.	
466 052 133 5	3.5 m
466 052 133 7	3.7 m
466 052 134	4.0 m
466 052 134 2	4.2 m
466 052 134 5	4.5 m
466 052 134 7	4.7 m
466 052 135	5.0 m
466 052 135 5	5.5 m
466 052 136	6.0 m

Female thread (DKR)

R+M Nr.	
466 054 133 5	3.5 m
466 054 133 7	3.7 m
466 054 134	4.0 m
466 054 134 2	4.2 m
466 054 134 5	4.5 m
466 054 134 7	4.7 m
466 054 135	5.0 m
466 054 135 5	5.5 m
466 054 136	6.0 m

Female thread (DKOL)

R+M Nr.	
466 072 133 5	3.5 m
466 072 133 7	3.7 m
466 072 134	4.0 m
466 072 134 2	4.2 m
466 072 134 5	4.5 m
466 072 134 7	4.7 m
466 072 135	5.0 m
466 072 135 5	5.5 m
466 072 136	6.0 m

Female thread (DKOL)

R+M Nr.	
466 076 133 5	3.5 m
466 076 133 7	3.7 m
466 076 134	4.0 m
466 076 134 2	4.2 m
466 076 134 5	4.5 m
466 076 134 7	4.7 m
466 076 135	5.0 m
466 076 135 5	5.5 m
466 076 136	6.0 m

Male thread (AGR)

R+M Nr.	
466 044 133 5	3.5 m
466 044 133 7	3.7 m
466 044 134	4.0 m
466 044 134 2	4.2 m
466 044 134 5	4.5 m
466 044 134 7	4.7 m
466 044 135	5.0 m
466 044 135 5	5.5 m
466 044 136	6.0 m



Field of application: self-service washing bays, roll at 200 m

R+M Nr.	TYP	DN	Ø	P	BP	°C
300 160 6	orange	6	12.8	200 bar	>800 bar	-40 °C - +60 °C