

- ✓ Integrated Recovery
- ✓ Temperatures up to 120°C
- ✓ High durability
- ✓ Multifunctional

The new Mosmatic Aqua Pro with an integrated water recovery system. This surface cleaner does not require an external industrial vacuum. Thanks to the venturi nozzle that is attached directly to the housing, wastewater can be discharged with a standard vac hose. The Aqua Pro can clean and recover or both at the same time.



TECHNICAL DATA


Pressure	350 bar
Temperature	120°C
Inlet	G3/8" F



FEATURES

Integrated recovery

The black anodized aluminum suction device collects the wastewater via the Venturi and double housing principal. Mount your export hose on the suction device and place it into the desired port to drain the water. The use of a vacuum system is no longer needed.



Rotor Arms

Can withstand up to 500 bar, are precision welded and balanced.



2cp2 (2 Arms / 2 Nozzles)  
Part No. 82.946 (ø470 mm)

Quality Swivel

High rpm stainless steel swivel, features reinforced self lubricated stainless steel ball bearings for improved performance. The dual spring based carbide seal system, guarantees long lasting operation under tough conditions.



DYCI Swivel

Part No. 55.253

Adjustable Height

Stainless steel frame for added stability. Optimize your cleaning results with the height adjustable housing.



Stainless Steel Caster (Premium Quality)

Four 100 mm stainless steel casters with custom mounting brackets, ensure easy maneuvering even in confined spaces.  
Part No. 80.956

HP Guns

1. HP-Gun = high pressure cleaning
2. HP-Gun = recovery function



Name	Part No.	ø	Weight	Swivel	Rotor Arm	Nozzles	HP-Gun	Casters
FL-SAR 520	80.769	520	20 kg	1x DYCI	2x 1/8" NPTF	2x 18.1503 / 1x #3*	2x	4x ø100

Accessories

Name	Part No.	Nozzles
Nozzles package	78.983	2x 1502 / 1x #2*

\* #2 and #3 internal nozzles self recovery